

# MV YUNGA



Year built June 2010  
Where built Oshima Japan  
Flag Hong Kong  
Callsign VRGZ5  
IMO / Official number 9414917  
Home port Hong Kong  
Vessels class Nippon Kaiji Kyokai NS\*, (BCM), Strengthen for heavy cargo loading where nos. 2&4 holds empty. MNS\* PSCM. Double hull construction applied in all holds.  
Type Semi open hatch/box shaped  
International GRT/NRT 29 104 mt / 15 527 mt  
Suez GRT/NRT 29 293,19 mt/ 28 882,18 mt  
Panama GRT/NRT 29 104 mt/ 24 170 mt  
Design draft 12,149 mtr/11,605 mtr/10,102 mtr  
Summer draft (sw) 50 806,00 mt on 12,149 mtr  
Summer draft (sw) timber N/A  
Tropical draft (sw) 52 170,00 mt on 12,402 mtr  
Freshwater draft 50 805,00 mt on 12,424 mtr  
Tropical draft (fw) 52 138,00 mt on 12,667 mtr  
Winter draft (sw) 49 445 mt on 11,896 mtr  
Winter draft (fw) timber N/A  
Dept moulded 17,150 mtr  
TPC 53,86 (summer)  
LOA/Beam 182,98 / 32,26 mtr

HOLD CAPACITY	Cubic capacity CBM Grain	Cubic capacity CBM Bale
Hold no. 1.	9 235 m3	9 136 m3
Hold no. 2.	12 581 m3	12 500 m3
Hold no. 3.	12 548 m3	12 471 m3
Hold no. 4.	12 548 m3	12 473 m3
Hold no. 5.	12 205 m3	12 118 m3
Total	59 117 m3	58 700 m3

Number of hold/hatches 5/5

Hatch size /Hold size LxW	Hatch size	Hold dim. Aft/Fwd
No. 1.	14,76 x 19,8 mtr	25mx5.1m,8mx25,8m
No. 2.	20,50 x 25,8 mtr	25,8mx25,8mx28,78m
No. 3.	20,50 x 25,8 mtr	25,8mx25,8mx28,78m
No. 4.	20,50 x 25,8 mtr	25,8mx25,8mx28,78m
No. 5.	20,50 x 25,8 mtr	25,8mx8,5mx29,88m

Type of hatch covers Folding type- Nakata Mccorperation  
Distance from waterline to top of hatchcoaming Basis 50 % bunkers- no holds flooded no1 = 12,9mtr, no2 = 12,7mtr, no3 = 12,5mtr, no4 = 12,3mtr, no5 = 12,1mtr.  
Distance waterline to highest point full ballast 36,56 mtr  
Distance tanktop to hatchcoaming 17,1 mtr  
Height of hatchcoaming 1,6 mtr  
Air draft 36,56 mtr  
Distance from bow to end of last hatch 150,78 mtr  
Free deck space  
Ballast capacity 20,231 m3, 2286 m3 in ch3 (only in port)  
Tanktop strength 1=22,0t/m2, 2=20,0t/m2, 3=26,5t/m2, 4=20,0t/m2, 5=22,0t/m2.  
Deck strength No cargo to be considered for deck  
Hatch cover strength ch1 = 41,0 Kn/m2, ch2 = 35,41 Kn/m2, ch3 = 34,3 Kn/m2, ch4 = 34,3 Kn/m2, ch5 = 34,3 Kn/m2.  
Ventilation Natural ventilation  
Logs/lumber/stanchions N/A  
Container capacity N/A  
Cargo gear IHI x 4 sets each 30 mt.  
Max outreach Approx abt 9,9 mtr (outside ship rail)  
Grabs. Type/capacity N/A

### Speed and consumption

Speed	13,5 laden/ballast on 28,9 mt/25,1 mt
Eco speed loaded	55 % load and laden 11,3 knots on 21,5 m mt/day
Eco speed ballast	55 % load and ballast 11,8 knots on 21,3 mt/day
In port	Idle FO =2,6mt/ DO = 0,20mt. Working FO =3,5mt/DO = 0,20mt.

Bunker capacity	IFO = 2 051,4 m3 LSMGO = 487,6 M3.
-----------------	------------------------------------

Main engine	MITSUI MAN B&W/6S50MC
Auxiliary Engines	3 x YANMAR 480kw 6EY18(A)L

ITF	Yes
CO2 fitted	Yes
Australien hold ladders	Yes
P&I Club	Gard
H&M Club (leading)	MS&AD
Nationality of officers and crew	Chinese

Communication	
Telephone	870773207872/765057910
Telefax	765057912
E-mail	<a href="mailto:VRGZ5@GLOBEMAIL.COM">VRGZ5@GLOBEMAIL.COM</a>

### **All details about and without guarantee.**

Speed and consumption are: in good weather condition and up to Beaufort force 4 and Douglas sea state 3. Calculation of vessels performance on both laden and ballast passages has to be based upon an average speed/consumption during weather days up to Beaufort 4 and Douglas sea state 3.

” Owners warrant the vessel is capable of maintaining and shall maintain from beginning sea passage to end of sea passage, excluding any voyage upto 36 hours duration, up to and including Beaufort Scale 4 and Douglass Sea State 3, with combined wave and swell heights NTE 1,25 m, without adverse currents, being on even keel and excluding periods during which reductions of speed for safety, congestion or reduced visibility etc.

Laden or ballast speed and consumption for period of weather in excess of Beaufort 4 and Douglas sea state 3 is to be expressly excluded from calculations.

Vessel has liberty to consume MDO when maneuvering, in/out of ports, starting auxiliary engine, navigation in shallow/restricted /congestion/poor visibility, canal, straits and rivers.

When planning to enter SECA, charterers to arrange well ahead of time to supply appropriate and sufficient IFO and MDO to enter and exit SECA with 4 days margin (for changeover and unpumpables). Before fixing for SECA charterers to ensure sufficient separate empty IFO tanks are available.

Any savings in consumption must be off-set against any reduction in speed, any savings in time must be off-set against any excess consumption, any savings in IFO must be off-set against increased MDO and vice versa, and any overall saving on individual passage(s) must be set off against any overall loss on other individual passage(s) cost and time to which (including any deviation time required to meet SECA requirements and/or National regulations in operation in port to which vessel is bound) including ballast exchange to be for Charteters account.

Under no circumstances will any claim be deducted from hire unless and until it has been agreed by both parties.

No comingling of different fuel suppliers in tank allowed.